

## HRK 125



Standard construction  
 EV regulating unit = to control 1 wire.  
 DB regulating unit = to control 1 or 2 wires.

4x EV regulating unit, 4x  
 underreflector and 2x  
 upperreflector

Working length	125 cm.
Heating	Under and upper
Standard sheet thickness	0,4 - 8 mm.
Maximum sheet thickness	20 mm.
Distance between reflectors (centre to centre)	15 – 620 mm.
Adjustable clamping bars	Standard equipped with 2 pieces
Weight	125 kg
Connection voltage	220 - 230 Volt.

## HR 125

Standard construction	1 reflector with 1 regulating unit
Working length	125 cm.
Heating	Under
Sheet thickness	0,4 - 6 mm
Weight	25 kg.
Connection voltage	220 - 230 Volt.



## HRT 125



Standard construction  
 EV regulating unit = to control 1 wire.  
 DB regulating unit = to control 1 or 2 wires.

2x EV regulating unit and 2x  
 underreflector

Working length	125 cm.
Heating	Under and upper
Sheet thickness	0,4 - 6 mm
Distance between reflectors (centre to centre)	15 – 620 mm.
Weight	90 kg.
Connection voltage	220 - 230 Volt.

## Diamond Polisher EF200

Maximum sheet thickness with single flame pass	20 mm.
Cut depth	0,5 mm.
Rotations speed diamondtool	24.000 RPM
Feed speed (meter per minute)	Variabel. (1.0 tbv PMMA / 2.0 tbv PC)
Maximum sheet size	+/- 3.000 mm. (with supportframe)
Connection voltage	230 V.
Weight	50 kg.
Milling angle or bevelled edge	No



## Flame Polisher 800

Standard construction EV regulating unit = to control 1 wire. DB regulating unit = to control 1 or 2 wires.	2x EV regulating unit and 2x underreflector
Working length	125 cm.
Heating	Under and upper
Sheet thickness	0,4 - 6 mm
Distance between reflectors (centre to centre)	15 – 620 mm.
Weight	90 kg.
Connection voltage	220 - 230 Volt.



## Fixture

Easy to adjust fixture to cool materials at any set angel (VMA).  
Extended versions a double adjusting-angle are also available (VMB). Our professional fixtures are provided with 2 adjustable parallel stops to hold the products into the right angle.  
Both sides of the jig are open to slide the products out of the fixture when a complicated item is made. There is an option for a calibrated protractor for consistent angle setting. Mobile underframes for ideal working height available



Distributed by

# Signtrade

www.signtrade.com

TOLL FREE - 800 SIGNTRADE | DUBAI - U.A.E. TEL : +971 4 2681828 | Fax : +971 4 2694328 | E-mail : info@signtrade.com  
UAE ★ KSA ★ QATAR ★ OMAN ★ BAHRAIN ★ KUWAIT ★ PAKISTAN ★ KENYA