



HP Latex R2000 Plus Printer

Unprecedented quality and colours² on rigid up to 2.49 m, for sustained production environments



Achieve amazing colours and media look and feel

- Help increase profitability with higher value rigid and flexible applications with vibrant HP Latex gamut.
- Gain versatility with HP Latex Ink—from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified, water-based HP Latex Inks that produce odorless prints.³

Expand your offering with the glossiest white¹

- Expand your portfolio into a wide range of applications with glossiest white that resists yellowing.¹
- No waste between white jobs⁴ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white—automatic recirculation and printhead cleaning eliminate manual purging.

Increase your productivity with smart printing

- Meet production peaks—get high-speed quality up to 28 outdoor boards/hr⁵ with belt system, smart vacuum.
- Drive high productivity with multi-board printing, assisted loading, and advanced queuing.
- Maximise uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.
- Maintain control of your production and costs with the help of HP PrintOS software tools.

For more information, please visit <http://www.hp.com/go/LatexR2000>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://hpllatexknowledgecenter.com/>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

¹ Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing over time based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples.

² Most vibrant colours based on internal HP testing, January 2018 compared to leading competitive printers under \$350,000 USD. Tested in High Quality print mode on rigid (white acrylic 12-pass, 6-colour, 120%). Internal HP testing with HP GamutViewer, Alpha Shapes=50000.

³ HP Latex Inks are UL ECOLOGO® Certified. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <http://www.ul.com/EL>). There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

⁴ When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.

⁵ Outdoor mode 3-pass, 70%. On 1.2 x 2.4 m boards.

Technical specifications

Print

Printing modes	22 m ² /hr - Indoor High Quality (12p 120%) 43 m ² /hr - Indoor Production (6p 110%) 86 m ² /hr - Outdoor (3p 70%) 36 m ² /hr - White Spot (100%) 16 m ² /hr - White Overflow/Underfloor (100%) 5.2 m ² /hr - 3 layers day & night
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)
Cartridge size	5 L (colours, HP Latex Optimizer, HP Latex Overcoat); 3 L (white)
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)
Long-term print-to-print repeatability	Average \leq 1.0 dE2000, 95% of colours \leq 2 dE2000 ²

Media

Handling	Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather
Rigid media size	297 x 420 mm to 2489 x 1220 mm (up to 2489 x 3050 mm with two sets of optional extension tables)
Roll size	60.9 cm to 2.49 m
Roll weight	Up to 100 kg
Roll diameter	Up to 25 cm
Thickness	Up to 50.8 mm

Applications

Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customised packaging, prototyping

Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

Dimensions (w x d x h)

Printer	5.10 x 2.04 x 1.75 m (printer); 5.10 x 3.64 x 1.75 m (including standard input and output tables)
Shipping	5.32 x 2.24 x 2.15 m
Operating area	8.7 x 7.23 x 3 m

Weight

Printer	1600 kg
Shipping	2800 kg

What's in the box

HP Latex R2000 Printer; HP Latex R Series White Upgrade Accessory Kit; HP Latex R2000 Roll Printing Accessory Kit with 98-in spindles (x2) and pneumatic gun adapter and table top roll holders (x2); HP 886 Latex Printheads; HP Latex Printhead Cleaning Kit; standard input and output tables; foot switch; HP Internal Print Server and displays (x2); printer maintenance kit; warranty and intro docs

Environmental ranges

Operating temperature	15 to 30°C
Operating humidity	20 to 70% RH (non-condensing)

Power

Consumption	10 to 12 kW (typical)
-------------	-----------------------

Certification

Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1, EN12100-1, EN ISO13849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)
Environmental	WEEE; RoHS (EU, China, Korea, Singapore, Turkey, Ukraine); India Waste Management Rules; REACH; CA 65 Prop; ErP Ecodesign Directive

Warranty

18 Months Maintenance and Support coverage: 6 months limited hardware warranty; 12 months HP Standard Service, Maintenance and Support. Warranty may vary by country as required by law. Go to <http://www.hp.com/support> to learn about HP service and support options in your region.

Ordering information

Product

K0Q46C	HP Latex R2000 Plus Printer
--------	-----------------------------

Accessories

T7V23A	HP Latex R2000 Extension Tables
Y6V16A	HP Latex R Series Edge Holders Kit

Original HP printing supplies

G0Z21A	HP 886 White Latex Printhead
G0Z22A	HP 886 Optimizer Latex Printhead
G0Z24A	HP 886 Latex Printhead
G0Z00A	HP 886 Latex Printhead Cleaning Kit
G0Z09A	HP 886 3-liter White Latex Ink Cartridge
G0Z10A	HP 882 5-liter Cyan Latex Ink Cartridge
G0Z11A	HP 882 5-liter Magenta Latex Ink Cartridge
G0Z12A	HP 882 5-liter Yellow Latex Ink Cartridge
G0Z13A	HP 882 5-liter Black Latex Ink Cartridge
G0Z14A	HP 882 5-liter Light Cyan Latex Ink Cartridge
G0Z15A	HP 882 5-liter Light Magenta Latex Ink Cartridge
G0Z16A	HP 882 5-liter Optimizer Latex Ink Cartridge
G0Z17A	HP 882 5-liter Overcoat Latex Ink Cartridge

Original HP large format printing materials

HP Premium Removable Gloss Adhesive Vinyl
HP Permanent Gloss Adhesive Vinyl
HP Durable Backlit Fabric (Take-back program)³
HP Backlit Polyester Film (Take-back program)³

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

If you want to extend the support beyond what's included: HOHX4AC HP Standard Service, Maintenance and Support extension contract
HOJR1AC HP Enhanced Service, Maintenance and Support extension contract
U95W05 HP Latex R series Level 3 Train to repair and maintain – 5 days training at HP
U9Z53E 3 Years Next Business Day with Defective Media Retention for HP Latex R2000 Plus
K0Q45-67269 HP Latex R series Expert spare parts uptime kit

ECO highlights

- Better for print operations—no hazard warning labels or HAPs, no special ventilation needed¹
- Better for the environment—HP designs end-to-end sustainability into large-format printing
- Water-based inks produce odorless prints²
- HP Latex Inks are UL ECOLOGO[®] and UL GREENGUARD GOLD Certified³

Please recycle large-format printing hardware and printing supplies. Find out how at our website: <http://www.hp.com/ecosolutions>

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ UL ECOLOGO[®] Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <http://www.ul.com/EL>). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>.

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

² Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

³ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See <http://www.HPLFMedia.com/hp/ecosolutions> for details.

